

Resultssets to resultstables revisited

Roger B. Newson r.newson@qmul.ac.uk http://www.rogernewsonresources.org.uk

Cancer Prevention Group, Wolfson Institute of Population Health, Queen Mary University of London

Presented at the 2025 UK Stata Conference, London, 11–12 September, 2025 Downloadable from the conference website at https://econpapers.repec.org/paper/boc/lsug25/

- ► A **resultsset** is a Stata dataset created as output by a Stata program.
- ► They are nowadays created in **resultsframes**[1], but can also be listed, written to a file, or overwritten over the input dataset.
- Resultsset-generating SSC packages include parmest, xcollapse, xcontract, descsave, xdir, xframedir, and xsvmat.
- ► And, like other Stata datasets, resultssets can be input into "SQL—like" operations, using append, merge, joinby, and cross in official Stata, or the SSC packages keyby, addinby, expgen, and xframeappend, to output secondary resultssets.

- ► A **resultsset** is a Stata dataset created as output by a Stata program.
- ► They are nowadays created in **resultsframes**[1], but can also be listed, written to a file, or overwritten over the input dataset.
- Resultsset-generating SSC packages include parmest, xcollapse, xcontract, descsave, xdir, xframedir, and xsvmat.
- ► And, like other Stata datasets, resultssets can be input into "SQL—like" operations, using append, merge, joinby, and cross in official Stata, or the SSC packages keyby, addinby, expgen, and xframeappend, to output secondary resultssets.

- ► A **resultsset** is a Stata dataset created as output by a Stata program.
- ► They are nowadays created in **resultsframes**[1], but can also be listed, written to a file, or overwritten over the input dataset.
- Resultsset-generating SSC packages include parmest, xcollapse, xcontract, descsave, xdir, xframedir, and xsvmat.
- ► And, like other Stata datasets, resultssets can be input into "SQL-like" operations, using append, merge, joinby, and cross in official Stata, or the SSC packages keyby, addinby, expgen, and xframeappend, to output secondary resultssets.

- ► A **resultsset** is a Stata dataset created as output by a Stata program.
- ► They are nowadays created in **resultsframes**[1], but can also be listed, written to a file, or overwritten over the input dataset.
- ► Resultsset—generating SSC packages include parmest, xcollapse, xcontract, descsave, xdir, xframedir, and xsvmat.
- ► And, like other Stata datasets, resultssets can be input into "SQL—like" operations, using append, merge, joinby, and cross in official Stata, or the SSC packages keyby, addinby, expgen, and xframeappend, to output secondary resultssets.

- ► A **resultsset** is a Stata dataset created as output by a Stata program.
- ► They are nowadays created in **resultsframes**[1], but can also be listed, written to a file, or overwritten over the input dataset.
- ► Resultsset—generating SSC packages include parmest, xcollapse, xcontract, descsave, xdir, xframedir, and xsvmat.
- ► And, like other Stata datasets, resultssets can be input into "SQL-like" operations, using append, merge, joinby, and cross in official Stata, or the SSC packages keyby, addinby, expgen, and xframeappend, to output secondary resultssets.

The resultsset-central dogma: datasets make resultssets make resultsplots and/or resultstables[2]

- ► Statisticians make their living producing **resultsplots** and/or
- And a string variable needs to be encoded to numeric in order to
- And a numeric variable needs to be decoded to string in order to
- Resultssets (unlike Stata tables and graphs) are therefore a
- ► SSC packages used include sencode[3], factext, and

The resultsset-central dogma: datasets make resultssets make resultsplots and/or resultstables[2]

- ► Statisticians make their living producing **resultsplots** and/or resultstables.
- And a string variable needs to be encoded to numeric in order to
- And a numeric variable needs to be decoded to string in order to
- Resultssets (unlike Stata tables and graphs) are therefore a
- ► SSC packages used include sencode[3], factext, and

The resultsset-central dogma: datasets make resultssets make resultsplots and/or resultstables[2]

- ► Statisticians make their living producing **resultsplots** and/or resultstables.
- ► And a string variable needs to be encoded to numeric in order to be plotted.
- ► And a numeric variable needs to be decoded to string in order to be tabulated.
- Resultssets (unlike Stata tables and graphs) are therefore a sensible common currency for results, as their variables can be used equally to make resultsplots and/or resultstables. encoding and/or decoding when necessary.
- ► SSC packages used include sencode[3], factext, and fvregen for encoding, and sdecode and its family of dependents bmjcip, factmerg, ingap, and insingap for decoding.

The resultsset-central dogma: datasets make resultssets make resultsplots and/or resultstables[2]

- ► Statisticians make their living producing **resultsplots** and/or resultstables.
- ► And a string variable needs to be encoded to numeric in order to be plotted.
- ► And a numeric variable needs to be decoded to string in order to be tabulated.
- ▶ Resultssets (unlike Stata tables and graphs) are therefore a sensible **common currency** for results, as their variables can be used equally to make resultsplots and/or resultstables. encoding and/or decoding when necessary.
- ► SSC packages used include sencode[3], factext, and fvregen for encoding, and sdecode and its family of dependents bmjcip, factmerg, ingap, and insingap for decoding.

The resultsset–central dogma: datasets make resultssets make resultsplots and/or resultstables[2]

- Statisticians make their living producing resultsplots and/or resultstables.
- ► And a string variable needs to be encoded to numeric in order to be plotted.
- ► And a numeric variable needs to be decoded to string in order to be tabulated.
- ► Resultssets (unlike Stata tables and graphs) are therefore a sensible **common currency** for results, as their variables can be used equally to make resultsplots and/or resultstables. encoding and/or decoding when necessary.
- ▶ SSC packages used include sencode[3], factext, and fvregen for encoding, and sdecode and its family of dependents bmjcip, factmerg, ingap, and insingap for decoding.

The resultsset-central dogma: datasets make resultssets make resultsplots and/or resultstables[2]

- ► Statisticians make their living producing **resultsplots** and/or resultstables.
- ► And a string variable needs to be encoded to numeric in order to be plotted.
- ► And a numeric variable needs to be decoded to string in order to be tabulated.
- ► Resultssets (unlike Stata tables and graphs) are therefore a sensible **common currency** for results, as their variables can be used equally to make resultsplots and/or resultstables. encoding and/or decoding when necessary.
- ► SSC packages used include sencode[3], factext, and fvregen for encoding, and sdecode and its family of dependents bmjcip, factmerg, ingap, and insingap for decoding.

- ► The SSC package xauto creates an extended version of the auto data supplied with official Stata.
- ▶ We will use it to generate a secondary xcollapse resultsset, containing statistics on the list of 10 quantitative variables price npm rep78 trunk headroom tons length turn displacement gear_ratio, broken down by origin of car model (US or non-US).
- ► We then convert the resultsset to a multi-page resultstable in a .docx document example1.docx.

- ► The SSC package xauto creates an extended version of the auto data supplied with official Stata.
- ▶ We will use it to generate a secondary xcollapse resultsset, containing statistics on the list of 10 quantitative variables price npm rep78 trunk headroom tons length turn displacement gear_ratio, broken down by origin of car model (US or non-US).
- ► We then convert the resultsset to a multi-page resultstable in a .docx document example1.docx.

- ► The SSC package xauto creates an extended version of the auto data supplied with official Stata.
- ▶ We will use it to generate a secondary xcollapse resultsset, containing statistics on the list of 10 quantitative variables price npm rep78 trunk headroom tons length turn displacement gear_ratio, broken down by origin of car model (US or non-US).
- ► We then convert the resultsset to a multi-page resultstable in a .docx document example1.docx.

- ► The SSC package xauto creates an extended version of the auto data supplied with official Stata.
- ▶ We will use it to generate a secondary xcollapse resultsset, containing statistics on the list of 10 quantitative variables price npm rep78 trunk headroom tons length turn displacement gear_ratio, broken down by origin of car model (US or non-US).
- ► We then convert the resultsset to a multi-page resultstable in a .docx document example1.docx.


The secondary resultsset to be converted

This was created by xframeappending 10 xcollapse resultsframes, one for each quantitative variable. We then sencoded the string ID variable idstr to create the variable quanvar:


Contains data Observations Variables		20 10		
	type	format		Variable label
				Quantitative variable
us	byte	%-8.0g	us	US or non-US model
N	byte	%8.0g		(count) X
mean	float	%8.2f		(mean) X
sd	float	%8.2f		(sd) X
p0	float	%8.2f		(min) X
p25	float	%8.2f		(p 25) X
p50	float	%8.2f		(p 50) X
p75	float	%8.2f		(p 75) X
p100	float	%8.2f		(max) X

We see that the dataset has 1 observation per quantitative variable per car model origin group (non–US or US), and data on statistics.


- This plot was produced from our resultsset, using the SSC packages sdecode, sencode, and eclplot.
- And there are many other things we can do with resultssets!
- However, today we concentrate on multi-page tables in . docx documents, which clinical trial committees like.




- ► This plot was produced from our resultsset, using the SSC packages sdecode, sencode, and eclplot.
- And there are many other things we can do with resultssets!
- ► However, today we concentrate on multi-page tables in . docx documents, which clinical trial committees like.



- ► This plot was produced from our resultsset, using the SSC packages sdecode, sencode, and eclplot.
- And there are many other things we can do with resultssets!
- However, today we concentrate on multi-page tables in .docx documents, which clinical trial committees like.



- ► This plot was produced from our resultsset, using the SSC packages sdecode, sencode, and eclplot.
- And there are many other things we can do with resultssets!
- ► However, today we concentrate on multi-page tables in . docx documents, which clinical trial committees like.



- ► Converting results to results tables has previously been
- ► The process usually starts with decoding, using the sdecode
- ► And it *always* ends with listing, using the SSC packages
- ► However, there may be other steps between decoding and listing,
- ► These steps convert a resultsset (with a primary key and 1

- ► Converting resultssets to resultstables has previously been discussed in Newson (2012)[4] and Newson (2023)[5].
- ► The process usually starts with decoding, using the sdecode family of SSC packages.
- ▶ And it *always* ends with listing, using the SSC packages docxtab (for tables in .docx documents) or listtab (for tables in Markdown, HTML, LATEX, plain TEX, or .rtf documents).
- ► However, there may be other steps between decoding and listing, involving reshapeing (long or wide), appending, merging, characterizing (to define table-column headers), inserting gap observations, and/or grouping rows into pages in multi-page tables.
- ► These steps convert a resultsset (with a primary key and 1 observation per result) to a dataset ready for listing (with a primary key and 1 observation per table row).

- ► Converting resultssets to resultstables has previously been discussed in Newson (2012)[4] and Newson (2023)[5].
- ► The process *usually* starts with decoding, using the sdecode family of SSC packages.
- ▶ And it *always* ends with listing, using the SSC packages docxtab (for tables in .docx documents) or listtab (for tables in Markdown, HTML, LATEX, plain TEX, or .rtf documents).
- ► However, there may be other steps between decoding and listing, involving reshapeing (long or wide), appending, merging, characterizing (to define table-column headers), inserting gap observations, and/or grouping rows into pages in multi-page tables.
- ► These steps convert a resultsset (with a primary key and 1 observation per result) to a dataset ready for listing (with a primary key and 1 observation per table row).

- ► Converting resultssets to resultstables has previously been discussed in Newson (2012)[4] and Newson (2023)[5].
- ► The process *usually* starts with decoding, using the sdecode family of SSC packages.
- ► And it *always* ends with listing, using the SSC packages docxtab (for tables in .docx documents) or listtab (for tables in Markdown, HTML, IATEX, plain TEX, or .rtf documents).
- ► However, there may be other steps between decoding and listing, involving reshapeing (long or wide), appending, merging, characterizing (to define table-column headers), inserting gap observations, and/or grouping rows into pages in multi-page tables.
- ► These steps convert a resultsset (with a primary key and 1 observation per result) to a dataset ready for listing (with a primary key and 1 observation per table row).

- ► Converting resultssets to resultstables has previously been discussed in Newson (2012)[4] and Newson (2023)[5].
- ► The process *usually* starts with decoding, using the sdecode family of SSC packages.
- ► And it *always* ends with listing, using the SSC packages docxtab (for tables in .docx documents) or listtab (for tables in Markdown, HTML, LATEX, plain TEX, or .rtf documents).
- ► However, there may be other steps between decoding and listing, involving reshapeing (long or wide), appending, merging, characterizing (to define table-column headers), inserting gap observations, and/or grouping rows into pages in multi-page tables.
- ► These steps convert a resultsset (with a primary key and 1 observation per result) to a dataset ready for listing (with a primary key and 1 observation per table row).

- ► Converting resultssets to resultstables has previously been discussed in Newson (2012)[4] and Newson (2023)[5].
- ► The process *usually* starts with decoding, using the sdecode family of SSC packages.
- ► And it *always* ends with listing, using the SSC packages docxtab (for tables in .docx documents) or listtab (for tables in Markdown, HTML, IATEX, plain TEX, or .rtf documents).
- ► However, there may be other steps between decoding and listing, involving reshapeing (long or wide), appending, merging, characterizing (to define table-column headers), inserting gap observations, and/or grouping rows into pages in multi-page tables.
- ► These steps convert a resultsset (with a primary key and 1 observation per result) to a dataset ready for listing (with a primary key and 1 observation per table row).

Steps in converting a resultsset to a resultstable

These 11 steps are given in the order in which they *usually* happen. There are SSC modules for each step.

Step type	SSC modules used	Importance
Decode non-key variables to table cells	sdecode and dependents	Semi-compulsory
Reshape to long	xrelong	Optional
Append extra table rows	xframeappend, factmerg	Optional
Characterize table columns	chardef,xrewide	Optional
Reshape to wide	xrewide	Optional
Merge in extra table columns	addinby,fraddinby	Optional
Decode key variables to table row label	sdecode and dependents	Semi-compulsory
Characterize table row label	chardef	Optional
Insert gap observations	insingap, ingap	Optional
Group observations into pages	ltop	Optional
List table	listtab, docxtab	Compulsory

The "Compulsory" step (listing) is always necessary. The 2 "Semi–compulsory" steps (decoding) are *nearly* always necessary. The "Optional" steps are *frequently* absent (because, fortunately, *most* tables are simple). To find out more about the SSC modules, use findit in Stata.

- ► We start making our resultstable by decoding our statistics variables.
- This is done using the msdecode module of the sdecode package, which can input multiple numeric statistics variables to output a string variable displaying a decoded "vector–statistic", like a variable range in parentheses.
- ► This creates new string variables stat1, stat2, stat3, and stat4, displaying, respectively, the sample number, the mean (with SD), the median (with IQR), and the range.
- ▶ We then use the module xrelong, an extension of reshape long, which creates a long version of our resultsset, with an extra labelled key variable statseq and a single displayed statistic value variable stat.
- ► This gives us a dataset with 1 observation per quantitative variable per car—origin group per displayed statistic, and data on the values of those statistics.

- ► We start making our resultstable by decoding our statistics variables.
- ► This is done using the msdecode module of the sdecode package, which can input multiple numeric statistics variables to output a string variable displaying a decoded "vector-statistic", like a variable range in parentheses.
- ► This creates new string variables stat1, stat2, stat3, and stat4, displaying, respectively, the sample number, the mean (with SD), the median (with IOR), and the range.
- ▶ We then use the module xrelong, an extension of reshape long, which creates a long version of our resultsset, with an extra labelled key variable statseq and a single displayed statistic value variable stat.
- ► This gives us a dataset with 1 observation per quantitative variable per car—origin group per displayed statistic, and data on the values of those statistics.

- ► We start making our resultstable by decoding our statistics variables.
- ► This is done using the msdecode module of the sdecode package, which can input multiple numeric statistics variables to output a string variable displaying a decoded "vector-statistic", like a variable range in parentheses.
- ► This creates new string variables stat1, stat2, stat3, and stat4, displaying, respectively, the sample number, the mean (with SD), the median (with IQR), and the range.
- ▶ We then use the module xrelong, an extension of reshape long, which creates a long version of our resultsset, with an extra labelled key variable statseq and a single displayed statistic value variable stat.
- ► This gives us a dataset with 1 observation per quantitative variable per car—origin group per displayed statistic, and data on the values of those statistics.

- ► We start making our resultstable by decoding our statistics variables.
- ► This is done using the msdecode module of the sdecode package, which can input multiple numeric statistics variables to output a string variable displaying a decoded "vector-statistic", like a variable range in parentheses.
- ► This creates new string variables stat1, stat2, stat3, and stat4, displaying, respectively, the sample number, the mean (with SD), the median (with IQR), and the range.
- ▶ We then use the module xrelong, an extension of reshape long, which creates a long version of our resultsset, with an extra labelled key variable statseq and a single displayed statistic value variable stat.
- ► This gives us a dataset with 1 observation per quantitative variable per car—origin group per displayed statistic, and data on the values of those statistics.

- ► We start making our resultstable by decoding our statistics variables.
- ► This is done using the msdecode module of the sdecode package, which can input multiple numeric statistics variables to output a string variable displaying a decoded "vector-statistic", like a variable range in parentheses.
- ► This creates new string variables stat1, stat2, stat3, and stat4, displaying, respectively, the sample number, the mean (with SD), the median (with IQR), and the range.
- ▶ We then use the module xrelong, an extension of reshape long, which creates a long version of our resultsset, with an extra labelled key variable statseq and a single displayed statistic value variable stat.
- ► This gives us a dataset with 1 observation per quantitative variable per car—origin group per displayed statistic, and data on the values of those statistics.

- ► We start making our resultstable by decoding our statistics variables.
- ► This is done using the msdecode module of the sdecode package, which can input multiple numeric statistics variables to output a string variable displaying a decoded "vector-statistic", like a variable range in parentheses.
- ► This creates new string variables stat1, stat2, stat3, and stat4, displaying, respectively, the sample number, the mean (with SD), the median (with IQR), and the range.
- ▶ We then use the module xrelong, an extension of reshape long, which creates a long version of our resultsset, with an extra labelled key variable statseq and a single displayed statistic value variable stat.
- ► This gives us a dataset with 1 observation per quantitative variable per car—origin group per displayed statistic, and data on the values of those statistics.

The code for decoding and reshaping to long

The code to do this was as follows:

```
msdecode N, gene(stat1);
msdecode mean sd, delim(" (") suff(")") gene(stat2);
msdecode p50 p25 p75, delim(" (" ", ") suff(")")
  gene (stat3);
msdecode p0 p100, pref("(") delim(", ") suff(")")
  gene(stat4);
lab def statseq 1 "N" 2 "Mean (SD)" 3 "Median (IOR)"
  4 "Range";
drop N mean sd p*;
xrelong stat, i(quanvar us) j(statseq) jlabel(statseq);
iformat statseg stat;
lab var statseg "Statistic sequence";
lab var stat "Statistic value";
desc, fu;
```

We start by using msdecode to decode our 8 numeric statistics to 4 string variables, drop the numeric variables, and use xrelong, with the option jlabel(statseq), to reshape the dataset to long (with labelled *j*-values). The SSC package jformat left-justifies the new variables.

The resultssetset decoded and reshaped to long

We listed the new long dataset:

4. | Non-US Range (6.24, 18.29)

```
. by quanvar: list us statseq stat, abbr(32) sepby(quanvar us);
-> guanvar = Price
    1. | Non-US N 22
2. | Non-US Mean (SD) 6384.68 (2621.92) | 3. | Non-US Median (IQR) 5759.00 (4499.00, 7140.00) |
 4. | Non-US Range (3748.00, 12990.00)
 5. I US N
                       52
 6. | US Mean (SD) 6072.42 (3097.10)
 7. | US Median (IQR) 4782.50 (4184.00, 6234.00)
 8. | US Range (3291.00, 15906.00)
-> quanvar = Fuel consumption (nipperkins/mile)
   us statseq stat
 1. | Non-US N 22
 2. | Non-US Mean (SD) 11.04 (2.93)
 3. | Non-US Median (IQR) 10.45 (9.14, 12.19)
```

The long format allows dissimilar vector-statistics to be stacked.

- ▶ We continued by using xrewide (an extension of reshape wide), with the options i (quanvar statseq) j (us) cjlabel (varname), to create a dataset with 1 observation per quantitative variable per output vector—statistic, and data on that statistic in non—US and US models (side by side).
- ▶ We then created a string row label variable rowlabel by sdecodeing statseq.
- ► We then inserted gap observations using insingap, adding a gap observation at the start of each quantitative variable.
- ► This creates a dataset with 5 observations per quantitative variable, the first a gap observation and the other 4 containing data on the 4 vector–statistics in non–US and US models.

- ▶ We continued by using xrewide (an extension of reshape wide), with the options i (quanvar statseq) j(us) cjlabel (varname), to create a dataset with 1 observation per quantitative variable per output vector—statistic, and data on that statistic in non–US and US models (side by side).
- ▶ We then created a string row label variable rowlabel by sdecodeing statseq.
- ► We then inserted gap observations using insingap, adding a gap observation at the start of each quantitative variable.
- ► This creates a dataset with 5 observations per quantitative variable, the first a gap observation and the other 4 containing data on the 4 vector–statistics in non–US and US models.

- ▶ We continued by using xrewide (an extension of reshape wide), with the options i (quanvar statseq) j (us) cjlabel (varname), to create a dataset with 1 observation per quantitative variable per output vector—statistic, and data on that statistic in non–US and US models (side by side).
- ► We then created a string row label variable rowlabel by sdecodeing statseq.
- ► We then inserted gap observations using insingap, adding a gap observation at the start of each quantitative variable.
- ► This creates a dataset with 5 observations per quantitative variable, the first a gap observation and the other 4 containing data on the 4 vector–statistics in non–US and US models.

- ▶ We continued by using xrewide (an extension of reshape wide), with the options i (quanvar statseq) j (us) cjlabel (varname), to create a dataset with 1 observation per quantitative variable per output vector—statistic, and data on that statistic in non–US and US models (side by side).
- ► We then created a string row label variable rowlabel by sdecodeing statseq.
- ► We then inserted gap observations using insingap, adding a gap observation at the start of each quantitative variable.
- ► This creates a dataset with 5 observations per quantitative variable, the first a gap observation and the other 4 containing data on the 4 vector–statistics in non–US and US models.

- ▶ We continued by using xrewide (an extension of reshape wide), with the options i (quanvar statseq) j (us) cjlabel (varname), to create a dataset with 1 observation per quantitative variable per output vector—statistic, and data on that statistic in non—US and US models (side by side).
- ► We then created a string row label variable rowlabel by sdecodeing statseq.
- ► We then inserted gap observations using insingap, adding a gap observation at the start of each quantitative variable.
- ► This creates a dataset with 5 observations per quantitative variable, the first a gap observation and the other 4 containing data on the 4 vector–statistics in non–US and US models.

The dataset reshaped to wide with added gap rows

The new dataset, when listed, started like this:

. list rowlabel stat0 stat1, abbr(32) subvar sepby(quanvar) clean noobs;

```
Ouantitative variable
                                    Non-US
                                                                US
                           Price:
                                    2.2
                                                               52
                        Mean (SD) 6384.68 (2621.92)
                                                               6072.42 (3097.10)
                     Median (IQR) 5759.00 (4499.00, 7140.00) 4782.50 (4184.00, 6234
                                  (3748.00, 12990.00)
                                                              (3291.00, 15906.00)
                            Range
Fuel consumption (nipperkins/mile):
                                    22
                                                               52
                        Mean (SD)
                                  11.04 (2.93)
                                                               13.61 (3.13)
                     Median (IOR)
                                  10.45 (9.14, 12.19)
                                                               13.47 (11.64, 15.53)
                            Range
                                  (6.24, 18.29)
                                                               (7.53, 21.33)
               Repair record 1978:
                                                               48
                        Mean (SD) 4.29 (0.72)
                                                               3.02 (0.84)
                     Median (IQR) 4.00 (4.00, 5.00)
                                                               3.00 (3.00, 3.00)
                                  (3.00, 5.00)
                                                               (1.00, 5.00)
                            Range
            Trunk space (cu. ft.):
                                   2.2
                                                               52
                        Mean (SD) 11.41 (3.22)
                                                               14.75 (4.31)
                     Median (IOR) 11.00 (9.00, 14.00)
                                                              16.00 (11.00, 17.00)
                            Range (5.00, 16.00)
                                                               (7.00, 23.00)
```

This looks *a bit* more like a resultstable! *However*...

- ▶ ... there are 5 observations (including gap observations) for each of 10 quantitative variables. These 50 rows might be too many for one page of our A4.docx output!
- Fortunately, the SSC package ltop ("lines to pages") creates a page sequence variable, grouping table rows into pages.
- ▶ ltop has an option maxlperp (#), specifying the maximum lines per page.
- ► It has an option iby (varlist), specifying internal by—groups that must not be split between pages.
- And it can have a weight expression, specifying that some table rows might be taller than others.

- ► ... there are 5 observations (including gap observations) for each of 10 quantitative variables. These 50 rows might be too many for one page of our A4 .docx output!
- ► Fortunately, the SSC package ltop ("lines to pages") creates a page sequence variable, grouping table rows into pages.
- ▶ ltop has an option maxlperp (#), specifying the maximum lines per page.
- ▶ It has an option iby (varlist), specifying internal by-groups that must not be split between pages.
- And it can have a weight expression, specifying that some table rows might be taller than others.

- ► ... there are 5 observations (including gap observations) for each of 10 quantitative variables. These 50 rows might be too many for one page of our A4 .docx output!
- ► Fortunately, the SSC package ltop ("lines to pages") creates a page sequence variable, grouping table rows into pages.
- ▶ ltop has an option maxlperp (#), specifying the maximum lines per page.
- ▶ It has an option iby (varlist), specifying internal by-groups that must not be split between pages.
- And it can have a weight expression, specifying that some table rows might be taller than others.

- ► ... there are 5 observations (including gap observations) for each of 10 quantitative variables. These 50 rows might be too many for one page of our A4 .docx output!
- ► Fortunately, the SSC package ltop ("lines to pages") creates a page sequence variable, grouping table rows into pages.
- ► ltop has an option maxlperp (#), specifying the maximum lines per page.
- ► It has an option iby (varlist), specifying internal by—groups that must not be split between pages.
- And it can have a weight expression, specifying that some table rows might be taller than others.

- ► ... there are 5 observations (including gap observations) for each of 10 quantitative variables. These 50 rows might be too many for one page of our A4 .docx output!
- ► Fortunately, the SSC package ltop ("lines to pages") creates a page sequence variable, grouping table rows into pages.
- ► ltop has an option maxlperp (#), specifying the maximum lines per page.
- ► It has an option iby (varlist), specifying internal by-groups that must not be split between pages.
- ► And it can have a weight expression, specifying that some table rows might be taller than others.

- ► ... there are 5 observations (including gap observations) for each of 10 quantitative variables. These 50 rows might be too many for one page of our A4 .docx output!
- ► Fortunately, the SSC package ltop ("lines to pages") creates a page sequence variable, grouping table rows into pages.
- ► ltop has an option maxlperp (#), specifying the maximum lines per page.
- ► It has an option iby (varlist), specifying internal by-groups that must not be split between pages.
- ► And it can have a weight expression, specifying that some table rows might be taller than others.

Example: Grouping rows into pages

We use ltop to create a new page sequence variable pageseq, with maximum lines per page set by maxlperp (40), inner by-groups corresponding to values of quanvar, and weights equal to gapobs+1, where gapobs is a binary indicator that an observation is a gap row. We then use xcontract to display numbers of rows on each page:

```
. ltop pageseq [weight=gapobs+1], iby(quanvar)
> maxlperp(40);
(frequency weights assumed)
```

. xcontract pageseq, list(, abbr(32));

	+		+	
	pageseq	_freq	_percent	
1.	1	30	60.00	
2.	2	20	40.00	
	1.		1.	

We see that 30 table rows are on Page 1 and that 20 are on Page 2. Note that the weights allow a gap row to be twice as tall as other rows.

- ▶ We now have a dataset with 1 observation per table row, with the rows grouped into pages.
- ► So, we can now write a document—generating section to write that dataset to a document example1.docx, looping over pages and creating a multi—page "Table XYZ".
- ▶ We can now have a look at our new document.

- ► We now have a dataset with 1 observation per table row, with the rows grouped into pages.
- ► So, we can now write a document—generating section to write that dataset to a document example1.docx, looping over pages and creating a multi—page "Table XYZ".
- ▶ We can now have a look at our new document.

- ► We now have a dataset with 1 observation per table row, with the rows grouped into pages.
- ► So, we can now write a document—generating section to write that dataset to a document example1.docx, looping over pages and creating a multi—page "Table XYZ".
- ▶ We can now have a look at our new document.

- ► We now have a dataset with 1 observation per table row, with the rows grouped into pages.
- ► So, we can now write a document—generating section to write that dataset to a document example1.docx, looping over pages and creating a multi—page "Table XYZ".
- ▶ We can now have a look at our new document.

References

- [1] Newson, R. B. Resultssets in resultsframes in Stata 16–plus. Presented at the 2022 London Stata Conference, 8–9 September, 2022. Downloadable from http://ideas.repec.org/p/boc/lsug22/01.html
- [2] Newson, R. Resultssets, resultsspreadsheets, and resultsplots in Stata. Presented at the 2006 German Stata User Meeting, 31 March, 2006. Downloadable from http://ideas.repec.org/p/boc/dsug06/01.html
- [3] Newson, R. B. Creating factor variables in resultssets and other datasets. Presented at the 19th UK Stata User Meeting, 12–13 September, 2013. Downloadable fron https://ideas.repec.org/p/boc/usug13/01.html
- [4] Newson, R. B. 2012. From resultssets to resultstables in Stata. The Stata Journal 12(2): 191–213. Downloadable from https://journals.sagepub.com/doi/pdf/10.1177/1536867X1201200203
- [5] Newson, R. B. Customized Markdown and .docx tables using listtab and docxtab. Presented at the 2023 London Stata Conference, 7–8 September, 2023. Downloadable from https://econpapers.repec.org/paper/boclsug23/01.htm

The presentation, and the example do-file, can be downloaded from the conference website. The packages can be downloaded from SSC.